

### 4.1.3 EUT RF Exposure

For BLE

#### Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.3	-1.0±1	0	1.000
Middle(2440MHz)	-0.42	-1.0±1	0	1.000
Highest(2480MHz)	-0.16	-1.0±1	0	1.000
GFSK(2Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.55	-1.0±1	0	1.000
Middle(2440MHz)	-0.64	-1.0±1	0	1.000
Highest(2480MHz)	-0.33	-1.0±1	0	1.000

Worst case: GFSK(1Mbps)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-0.3	-1.0±1	0	1.000	0.310	3.0
Middle (2440MHz)	-0.42	-1.0±1	0	1.000	0.312	
Highest (2480MHz)	-0.16	-1.0±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200300128E-01.